KEEP OUT OF REACH OF CHILDREN
READ SAFETY DIRECTIONS BEFORE OPENING OR USING

ENSYSTEX

LEADING INNOVATION IN PEST HANAGEHENT

FUMITHOR THORT

DISINFECTANT SMOKE GENERATOR

ACTIVE CONSTITUENT:
35 a/ka GLUTARALDEHYDE 200 a/ka ORTHO-PHENYLPHENOL

ALSO CONTAINS: 190 g/kg POTASSIUM CHLORATE

Net Contents: 100 g



OXIDIZING



HARMFUL



DANGEROUS FOR THE ENVIRONMENT

GENERAL INSTRUCTIONS

Calculate the number of cars to be used. Seal closed any possible air leaks from the premises and place the container on the floor away from any flammable materials. Remove the plastic cap and the green plastic tube, and light the wick. Do not remove the metal lid. The area to be treated should be evacuated beforehand and duly marked with a sign to prevent unauthorised entry. For best results, ignite the generator late in the evening and leave area closed overnight. Place the generator on a fireproof base, a protective floor covering or in a metal bucket. To ignite, using a match, light the wick. Always ignite those generators furthest away, lighting those penerators your exit last. Leave immediately after lighting generators. The generator will burn for approximately 1 minute 30 seconds, however keep area articipatif for at least 6 hours after lighting. Ventilate for 30 minutes before re-entry.

PRECAUTIONS

DO NOT use in premises when animals are present.

Remove or cover exposed food, food utensils, food processing areas, pet bowls and fish tanks. Aerators should be turned off while the product is in use and while the aquarium is covered.

DO NOT apply where smoke detectors are installed, or turn them off prior to use.

PROTECTION OF WILDLIFE, FISH, CRUSTACEANS AND ENVIRONMENT

Harmful to aquatic organisms, may cause long-term adverse effects. Fish tanks and aquariums should be removed or covered prior to use of this product. D0 NOT contaminate streams, rivers or waterways with the product or used containers.

STORAGE AND DISPOSAL

Store in the closed, original container in a dry, cool, well-ventilated area out of direct sunlight. Keep away from combustible materials. Dispose of used generator safely, wrap empty can in paper and place in waste bin. D

SAFETY DIRECTIONS

Harmful if inhaled. Irritant to the respiratory system, skin and eyes. Sensitisation by inhalation and skin contact. DO NOT inhale smoke. Avoid contact with skin. Wear suitable gloves. Irritating to eyes. Leave immediately after lighting generators. Thoroughly ventilate treated areas before re-occupying.

FIRST AID

If poisoning occurs, contact a doctor or Poisons Information Centre. Phone Australia 13 11 26; New Zealand 0800 764 766.

L-AU- CHEFS1001 1.02 02.16

CUSTOMER SERVICE / EMERGENCY RESPONSE (ALL HOURS) 13 35 36

MATERIAL SAFETY DATA SHEET

Additional information is listed in the Material Safety Data Sheet which is available from Ensystex on request. Call Customer Service on 13 35 36 or visit our web site at www.Ensystex.com.au.

NOTICE

Ensystex warrants that this product conforms to its chemical description and is reasonably fit for the purposes stated on the label when used in accordance with Directions for Use under normal conditions of use. No warranty of merchantability or fitness for a particular purpose, express or implied, extends to the use of the product contrary to label instructions, or under abnormal conditions.

of direct abnormal conditions.			
	SITUATIONS	CONTROLS	RATE
	Residential, Commercial, industrial, agricultural, and public services buildings including food handling premises	Gram positive and gram negative bacteria, fungal and bacterial spores, yeasts, algae and viruses.	1 generator/200 m ³

ENSYSTEX AUSTRALASIA PTY LTD ABN 53 102 221 965 Unit 3 The Junction Estate

Unit 3 The Junction Estate 4-6 Junction Street AUBURN NSW 2144 www.ensystex.com.au ENSYSTEX NEW ZEALAND LTD 17C Corinthian Drive, Albany,

Auckland 0752
Tel: 0800 ENSYSTEX (0800 367 978)
www.ensystex.co.nz

See bottom of can for batch number and Date of Manufacture

Approved pursuant to the HSNO Act 1996, Approval Code: HSR002590. See www.epa.govt.nz for approval conditions.

™ Trademark of Ensystex, Inc. used under licence.